


NOTES:
ELECTRICAL:
1:RATED CURRENT: 3A Max.
2:RATED VOLTAGE: 30V DCR(RMS),
3:WIRE IN HOLD FORCE 5N (20#WIRE) MIN
4:INSULATION RESISTANCE: 100 MEGADHMS MIN.
SIDELECTRIC WITHSTANDING VOLTAGE: 1200 VAC Min.
MECHANICAL:
ENVIRONMENTAL:
TEMPERATURE RANGE: -40°C TO 70°C.

X.	±0.35	X.*	±5°
X	±0.30	X.*	±2.5°
.XX	±0.25	.XX*	±1.5°

TOL TABLE:

MODEL NAME: (PART NO.)	WP8-28
DESIGN:	LingZhifeng 04/27'18
CHECKED:	Jack Zhou 04/27'18
APPROVED:	HuXiaoQu 04/27'18

FINISH:	See table
QTY: /	
DWG NO.:	
UNIT:	mm
VIEW:	
SCALE:	5:1
SHEET:	1/1
REV.:	A
SIZE:	A3


 广东正宝科技有限公司
 GUANGDONG TRENPRO TECHNOLOGY CO., LTD.

REV:	ECN NO.	MODIFIED MARK	APPROVED
A	20180427002	FIRST RELEASE	Jack Zhou