

PANEL CUT OUT


- NOTES:
- ELECTRICAL:
 - 1: RATED CURRENT: 0.2A Max.
 - 2: RATED VOLTAGE: 50V AC.
 - 3: CONTACT RESISTANCE: 30 MILLIOHMS Max. AFTER TESTING: 100 MILLIOHMS Max.
 - 4: INSULATION RESISTANCE: 100 MEGAOHMS Min.
 - 5: DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC Min.
 - MECHANICAL:
 - 1: INSERTION FORCE: 3N-30N.
 - 2: WITHDRAWAL FORCE: 3N-30N.
 - 3: DURABILITY: 100 CYCLES.
 - ENVIRONMENTAL:
 - TEMPERATURE RANGE: -20°C TO 60°C.

NO.	PART NAME	Q'TY	MATERIAL	FINISH/COLOR	REMARK
⑦	WASHER	1	PBT	BLACK	
⑥	SOCKET	1	BRASS	Au PLATING	
⑤	HOUSE	1	PPO	BLACK	
④	TERMINAL-C	1	BRASS t=0.5	Sn PLATING	RoHS
③	TERMINAL-B	1	BRASS t=0.4	Sn PLATING	
②	TERMINAL-A	1	BRASS t=0.5	Sn PLATING	
①	SHELL	1	BRASS t=0.2	Sn PLATING	

ANGLE	PART NAME	Q'TY	MATERIAL	FINISH/COLOR	REMARK
63 < L				±5	
16 < L ≤ 63				±0.5	
4 < L ≤ 16				±0.4	
L ≤ 4				±0.3	
				±0.2	

TOL TABLE:	See table				
FINISH:	See table				
Q'TY: /	See table				
DESIGN:	Z.F.Lion	10/09'19			
CHECKED:	L.W.Wu	10/09'19			
APPROVED:	Q.Hu	10/09'19			

MODEL NAME:	RCA-132P				
(PART NO.)					
TITLE:	RCA PIN JACK				
DWG NO.:					
UNIT:	mm				
VIEW:					
SCALE:	5:1				
SHEET:	1/1				
SIZE:	A3				



REV.:	ECN NO.:	MODIFIED MARK:	APPROVED:
A		FIRST RELEASE	